

SPECIFICATION SHEET

Specifications

PDU consists of 28 C13 and 4 C19 outlets for output and IEC 309 plug for input. Designed to be vertically mounted to standard 19" server racks and cabinets by means of cage nuts. 2 meters long power cord. Unit has a black powder coated finish. The power unit requires 250 input volts. PDUs are equipped with meters that can be monitored remotely through connection to SNMP, SMTP, Telnet.



Technical Information

Dimensions:

110 mm (4.33") D, 65 mm (2.55") W, 1550 mm (61") H

Material:

Plastic construction

Compliance:

RoHS, CE

Load Rating:

32 Amp load, 250 Volt input

Packaging:

Pre-built, Ready-to-install

Key Features

Mounting:

Vertically mounted

Input Plug:

IEC 309

Output Plugs:

28 X C13, 4 X C19

Safety and Monitoring:

Metered with Twist-Locking IEC 309 Plug. C13 Output plugs are equipped with locking mechanism.

TSDI Power Distribution Unit

110mm(4.33")D, 65mm(2.55")W, 1550mm(61")H



Output – 28 X C13 Port, 4 C19 Port



Meter



Input Plug – IEC 309

DISCLAIMER: 2M Power cord (1840mm to be exact) measures from the termination point up to the input plug.